

**고장력강/ 디지털/ 대용량
판금 스포트 용접기**
High Strength Steel / Digital
/ Large capacity Spot Welder

Model No.
SY-SW12000HD

고강도철판 차체까지 완벽하게 판금 용접

고강도철판에도 자동함마 작업 가능

- I 최신형 고장력강 차체까지 완벽하게 판금 용접
 - I DC 전류 방식 채용으로 출력 효율 극대화
 - I 마그네트 비상 교체를 대비한 예비 마그네트 내장으로 작업 중단 사전 예방
 - I 터치 프리 용접 기능 실현으로 양손 사용이 더욱 자유로워짐
 - I 디지털의 편리함과 아날로그의 안정성을 결합
 - I 작업 유형별 최적의 용접 시간이 원-터치로 자동 세팅
 - I 용접의 안정성과 일관성을 위한 아날로그 제어방식의 4단계 선택터
 - I 대용량 장비의 손쉬운 이동을 위한 효율적 기구 설계
 - I 작업 공간의 활용도를 높일 수 있는 빌트인 액세서리 수납함
 - I 효율적 판금 작업의 필수품 자동 슬라이드 함마 사용 가능
 - I 첨단 마이크로컴퓨터를 내장한 정밀하고 정확한 용접 시간 제어
-
- I Perfectly spot weld the latest high tensile steel car body
 - I Maximize output power efficiency by adopting DC current method
 - I The built-in spare magnet device for emergency replacement realize prevention of work stoppage
 - I Touch free weld function make both hands more flexibly use
 - I A winning combination of digital convenience and analogue stability
 - I Between efficiency in use and exclusive of design
 - I There are three major advantages of the design, namely steady performance, simplicity and user-friendliness

- I One-touch set of optimum time for each weld type
- I Analog controlled weld capacity selector realizes steady and constant weld performance
- I Highly effective structure for easy access of heavy welder
- I Built-in accessory rack for availability in working space



신제품

Specifications

제품명	판금 스포트 용접기 (고장력강/ 디지털/ 대용량)
모델명	SY-SW12000HD
입력전압	단상 AC 380V, 50/60Hz, 12kVA
출력전압	12 ~ 16V
출력전류	최대 DC 7200A
용접능력	1.4mm 철판 2장
설정기능	용접용량: 4단 용접시간: 10단, 최대 1초 용접유형: 5종 - 단면 용접 - 양면 용접 - 자동함마 & 와샤 용접 - 반복 용접 - 시보리 작업
안전장치	직류저전압구동방식
제품크기	(W)560 x (L)640 x (H)900mm
제품무게	약 125kg
공급액세서리	입력선 8m, 출력선 2.5m x 2 총알팁, 여스타입, 시보리팁, 부채팁, 와샤팁, 수동 풀러, 자동 슬라이드 함마 각1개씩

Product name	Car body repair digital spot welder (High Strength Steel/ Digital/ Large capacity)
Model No.	SY-SW12000HD
Power source	Single phase, AC 380V, 50/60Hz, 12kVA
Output Voltage	12 ~ 16V
Output current	MAX, DC 7200A
Weld capacity	2 sheets of 1.4mm Metal sheet
Adjustable	Weld capacity: 4 steps
functions	Weld time: 10 steps, Max, 1sec Working type: Single-sided weld, Double-sided weld, Slide hammer and washer weld, Repeated weld, Contact shrinking
Safety device	DC low voltage driving gear type
Dimension	(W)560 x (L)640 x (H)900mm
Weight	Approx. 125kg
Standard accessories	Input power cord 8m, Output cord 2.5m x 2, Pointed tip, Earth tip, Flat faced tip, Flat swivel tip, Washer tip, Rapid puller, Automatic slide hammer teach